


# [ Multi Spans ]



- Hoop to Ground Tube Locking and Tensioning System which provides full cover tensioning facility whilst locking hoop to ground tube.
- Aluminium grip rail fitted to gutters as standard. No timbers used or drilling required.
- Heavy duty galvanised steel gutters, give workable access.
- All multi spans available with straight sides vertical to 2.44m if required.



- Independent central gutter posts supporting heavy duty galvanised steel 280mm wide gutters.

# [ Horticulture Growing Houses ]



## 6.55m (21'6") Spans

- Hoop Diameter - 50mm
- Ridge/Diagonals - 50mm
- Gutter posts - 50mm
- Timber Frame Ends - 75 x 75mm
- Hoop Spacing - 2.44m (8ft)
- Designed Windspeed - 100mph



## 8.08m (26'6") Spans

- Hoop Diameter - 60mm
- Ridge/Diagonals - 50mm
- Gutter posts - 60mm
- Timber Frame Ends - 75 x 75mm
- Hoop Spacing - 2.44m (8ft)
- Designed Windspeed - 100mph
- Steel end frames with aluminium grip rails are optional on 1.68m structures.



2.28m Straight sided structures come with steel end frames with aluminium grip rails plus cross and knee bracing as standard.



National PolyTunnels Ltd, 4 Cable Court, Pittman Way,  
 Fulwood, Preston, Lancashire PR2 9YW.  
 Tel: 01772 799200 Fax: 01772 799250  
 Email: sales@nationalpolytunnels.co.uk

Information is correct at the time of issue, however we reserve the right to change design/specifications without prior notice.

# Horticulture Growing Houses